

EARLES LINSEED OIL MATT. A BREATHABLE WATER BASED COATING SUITABLE FOR BOTH INTERIOR AND EXTERIOR APPLICATION

PRODUCT DESCRIPTION

Linseed Oil Matt Emulsion is a traditional decorative and protective coating for plinths, barns, fences, sheds and all woodwork giving a water resistant, flexible coating, with high opacity, longevity and easy application.

Linseed Oil Matt Emulsion also gives good adhesion to primed steel and old concrete.

PRODUCT FEATURES

- Long lasting
- Environmentally friendly
- No harmful fumes in use
- Breathable
- Plastic free
- Weather resistant

COLOUR RANGE

As per colour card

PAINT FINISH

Matt finish

STORAGE AND SHELF LIFE

Store in a dry location in original containers between 5°C and 25°C. 12 Months in unopened containers.

DRYING TIME

Water resistant in 1 hour at 20°C,
3-7 days for full drying, weather dependent.

OVERCOATING TIME

24 hours

THEORETICAL SPREAD RATE

8m² per litre per coat

COATS

Recommended 3 coat system, (1 priming coat, 2 full coats)
See application guidelines sheet for full application instructions.

PACK SIZE

2.5 and 5 Litre tins

THINNER/CLEANER

Water

APPLICATION METHOD

Brush (recommended) or medium pile roller

CLEANING

Clean all equipment with fresh water immediately after use.

DISPOSAL

Dispose of in accordance with local authority requirements.

Do not allow the product to enter watercourses or drains or dispose of where ground or surface waters may be affected. All waste material including empty containers are controlled wastes and should be disposed of in accordance with the regulations under The Control Of Pollution Act. Using information provided in this data sheet advice should be obtained from the waste regulation authority whether the special regulations apply.

SAFETY PRECAUTIONS

Application materials and soiled rags may self ignite without warning. Dispose of safely by laying flat and allowing to dry or clean with warm soapy water to avoid fire risks.

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- If medical advice is needed, have product container or label at hand.

RESPIRATORY PROTECTION:	Wear a dust mask.
HAND PROTECTION:	Wear protective gloves.
SKIN PROTECTION:	Cover arms and legs.
EYE PROTECTION:	Wear suitable safety glasses
IF SWALLOWED:	Do not induce vomiting. Seek medical advice if ingested or if an allergic reaction occurs.

PRODUCT ASSISTANCE

Contact Northern Paints and Coatings Ltd:

Email: sales@npc-ltd.co.uk or phone: +44(0)1665 494034

www.npc-ltd.co.uk

Important: The content of this documentation is based on our experience of the product. The company guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application including non-use of the company's approved application tools, application by non-competent personnel, use of products not compatible with the company's products or bad weather conditions. For further information, refer to the material safety data sheet.