



Baseline Information
This drawing is based on Murdoch Wickham drawing 14558/ALMT/LS/5703 Allotment Area C Layout

Health & Safety Comments
No specific comments

General Notes
Weld Mesh Fence
Jackson Euroguard 1.83m high flatform medium weld mesh fence is to be galvanised and powder coated, colour Green RAL 6005 (or similar and approved), with matching single and double access gates. Installation is to be to the manufactures recommendations.
Attach Jacksons 600mm x 31mm 50m Roll 1.0mm (19g) galvanized wire rabbit protection netting to the base of the weld mesh fence with 300mm buried into the ground. Rabbit fencing to be clipped to the weld mesh fence at 300mm centres.
www.jacksons-fencing.co.uk

- Legend**
- Hoggin surface with timber edge
 - Bitumen macadam surface, refer to engineers details
 - Reinforced grass surface, refer to engineers details
 - Concrete slab base with timber retainer to storage sheds and supply stores
 - 1.83m high weld mesh fence with matching double / single access gates & rabbit proof fencing to base
 - Watering point - tap fitted with non return valve and fixed to timber post 100 x 100mm section
 - Watering point - galvanised steel allotment dip tank 1200x610x610mm with service box & float valve to be positioned over the hoggin surface www.cityirrigation.co.uk
 - 400x400mm PCC paving slab beneath each watering point
 - Non fixed paving slab to each allotment for plot numbers
 - Timber sleepers
 - 1 x 1m Albany tool sheds to sit on a concrete slab base, built in banks of 6-8 units with common walls (or similar and approved) www.albanysheds.co.uk
 - Woodscape Cleveland Picnic Set or similar approved (surface fixed) www.woodscape.co.uk
 - +57.5 Indicative levels



Green weld mesh fence



Banks of Albany Sheds, also showing turf path allotment partitions



Tap with upstand on 400x400mm PCC paving slab



Galvanised steel allotment dip tank



Outdoor lockable notice board attached to bottom right column of sheds as indicated, to be supplied by Wonderwall Products Ltd. or similar approved wonderwallproducts.co.uk

Condition 13 Allotments

No works relating to construction of the allotments hereby approved shall take place until the following have first been submitted to and approved in writing by the Local Planning Authority:
a) Details of edging to the paths;
b) Details Instant turf rolls to form allotment partitions;
c) Tap and trough specifications;
d) Location of water meter and provision of stopcock for the metered supply;
e) Details of soil specification, depth and quality, and details of remediation/testing proposed;
f) Details and specifications of allotment sheds; and
g) Details of rabbit-proof mesh fencing.

Rev P4 04.11.25 Issued for planning
Rev P3 10.10.25 Issued for planning
Rev P2 02.09.25 Issued for planning
Rev P1 13.02.25 Issued for planning

Revisions

MURDOCH WICKHAM
THE LANDSCAPE ATELIER

The Tide Barn
Bradbourne House
East Malling
Kent
ME19 6DZ
01732 752780
mail@murdochwickham.com
www.murdochwickham.com

Job Title
Arborfield Garrison, Infrastructure

Client
Crest Nicholson Chiltern

Drawing Title
Allotment Area C Hard Landscape Plan

Date **13 February 2025**
Scale **1:250 @ A1**
Drawn **NC**

Drawing no. 14558/SP/LS/5005	Rev. P4
--	-------------------