



NOTES	
1. DO NOT SCALE THIS DRAWING ON PRINT OR ELECTRONICALLY. WORK FROM FIGURED DIMENSIONS ONLY.	
2. No deviation from the details shown on this drawing is allowed without IESIS's prior permission in writing.	
3. Read the drawings with all Architects, Service Engineers and IESIS's relevant details and drawings. NE - Bring out dimensions as per the Architects drawings and precedence.	
4. All work is to be in accordance with the relevant specifications issued by IESIS, British Standard Codes of Practice, Statutory requirements and the Contract Documents.	
5. DRAWING STATUS	
P - PRELIMINARY - Evolving drawings for approvals, Tenders, Billings, etc.	
C - CONSTRUCTION - Fully developed drawings issued under instruction for construction.	
ONLY STATUS C DRAWINGS TO BE USED FOR CONSTRUCTION	
6. SUITABILITY CODE	
WORK IN PROGRESS	
S9 - Work in progress	
SHARED (NON-CONTRACTUAL)	
S1 - For coordination, S2 - For information, S3 - For internal review and comment, S4 - For construction approval	
DOCUMENTATION (FOR CONTRACTOR PURPOSES)	
D1 - For costing, D2 - For tender, D3 - For contractor design, D4 - For construction (Procurement)	
CONSTRUCTION	
A - For construction, B - For construction but with comments (i.e. areas in abeyance), C - Comprehensive reasons required.	

ADOPTABLE STREET LIGHTING TO WOKINGHAM DC SPECIFICATION (PART OF S38 APPLICATION)	
	STREET LIGHTING ON INFRASTRUCTURE (SPINE ROAD BY OTHERS (CREST ROAD))
	ADOPTABLE S38 LIGHTING: Street Light column: 6 metres, Conical tapered to WBC specification Aluminium, column colour grey, Painted: Factory standard, Post top mounting, 0 degrees luminaire: 85, Philips BGP702 Micro Lume, colour temperature neutral white
PRIVATE LIGHTING:	
	PRIVATE LIGHTING COLUMN TO HIGH STREET: Street Light column: 6 metres, Conical tapered Aluminium, column colour grey, Painted, Factory standard, Post top mounting, 0 degrees luminaire: 85, Philips BGP702 Micro Lume, colour temperature neutral white
	PRIVATE LIGHTING DESIGN TYPE A: Serra Solaflex, 40° Panel Tilt, 18 x 3K LED Array at Optic, RAL7046 Grey Finish, PIR Detector 6m T.L.S Tubular Steel Rooted Column, RAL7046 Grey Finish
	PRIVATE LIGHTING DESIGN TYPE B: Serra Solaflex, 40° Panel Tilt, 18 x 3K LED Array at Optic, RAL7046 Grey Finish, PIR Detector 6m T.L.S Tubular Steel Rooted Column, RAL7046 Grey Finish
	PRIVATE LIGHTING DESIGN TYPE C (BOLLARD): Krypton 160, 160mm, Conical Top, 500mA 3K Symmetric LED Array, RAL7046 Grey Finish
	PRIVATE LIGHTING DESIGN TYPE D: Krypton Pro S1 8 LED 3K 82 450mA, RAL7046 Grey Finish, 300mm Photocell 6m T.L.S Tubular Steel Rooted Column, RAL7046 Grey Finish



P1	ISSUED FOR APPROVAL	07.04.26	KW
Status/	Description	Date	By

IESISCIVILS

20 IRONMONGER LANE | LONDON | EC2V 8EP | UK
0207 600 2912
www.iesisgroup.com

Job Title	ARBORFIELD GREEN, DISTRICT CENTRE, PARCELS A,B,C & D
Client	TAYLOR WIMPEY WEST LONDON

SITE WIDE LIGHTING LAYOUT

Drawn	date	scale @ A0	C1 checked	WMA Project No.
KW	MAR26	1:500	-	SE2381

Orig No.	22585-50-05	Suitability	Status/Revision
		S2	P1

SCALE - 1:500

