

Installation Type	Unit of Measure	Capacity/Flow rate (1)	Use Factor (2)	Fixed use (litres/person/day) (3)	Litres/person/day = [(1)x(2)] + (3) (4)
WC (single flush)	Flush Volume (litres)		4.42	0.00	0
WC (dual flush)	Full flush Volume (litres)	6	1.46	0.00	8.76
	Part flush Volume (litres)	3	2.96	0.00	8.88
WC (multiple fittings)	Average effective flushing Volume (litres)		4.42	0.00	0
Taps (excluding kitchen/utility room taps)	Flow rate (litres/min)	7.00	1.58	1.58	12.64
Bath (where shower also present)	Capacity to overflow(litres)	149.00	0.11	0.00	16.39
Shower (where bath also present)	Flow Rate(litres / minute)	7.60	4.37	0.00	33.21
Bath Only	Capacity to overflow(litres)		0.50	0.00	0
Shower Only	Flow Rate (litres/minute)		5.60	0.00	0
Kitchen/Utility room sink taps	Flow rate (litres/minute)	3.70	0.44	10.36	11.99
Washing Machine	(Litres/kg dry load)	5.55	2.1	0.00	11.66
Dishwasher	(Litres/place setting)	0.60	3.6	0.00	2.16
Waste disposal unit	(Litres/use)	☒ Present	3.08	0.00	3.08
Water Softener	(Litres/person/day)	0.20	1.00	0.00	0.20
	(5)	Total Calculated use (litres/person/day) =SUM(column 4)			108.97

	(6)	Contribution from greywater (litres/person/day)	0
	(7)	Contribution from rainwater (litres/person/day)	0
	(8)	Normalisation factor	0.91
	(9)	Total internal water consumption = [(5)-(6)-(7)]x(8) (litres/person/day)	99.16
	(10)	External water use	5.0
	(11)	Total water consumption (Building Regulation 17.K) =(9)+(10)(litres/person/day)	104.2

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Burlington Riviera	17.64
Washing Machines	Siemens IQ500	17.157
Dishwasher	Siemens IQ100 Integrated	4.5



©Water Research Centre Limited 2026

[Terms and Conditions](#)
[System Requirements](#)